

# RG-EW300 PRO 300Mbps Wireless Smart Router

DATASHEET



# / Highlights

- Stronger signal with 4 x 5dBi antenna and signal amplifiers
- Easy management, easy life
- Life-time free cloud management supported

## **/** Highlight Features



### **Stronger Signal than the Average**


Equipped with signal amplifiers (FEM), four 5dBi omnidirectional antennas guarantee you efficient and stable connections.





# **/** Highlight Features

#### **WISP & Repeater Mode Supported**


Newly-added WISP & Repeater mode can amplify Wi-Fi signals to wider range. Enjoy whole-room WiFi coverage and lag free network.







# **/** Highlight Features



. . . . . . . . . . . . . . . . .

	Basic
Dimensions(W×D×H)	210 mm × 180 mm × 33 mm (8.27 in. × 7.09 in. × 1.3 in. antennas not included)
Weight	0.2615 kg (packages not included)
Wi-Fi Standards	Wi-Fi 4 (802.11n)
MIMO	2.4 GHz, 2×2, MIMO
Max. Speed	2.4 GHz: 300 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz
Antennas	4
Antennas Type	External Omnidirectional
Antenna Gain	2.4 GHz: 5 dBi
WAN Port	1, 10/100 Base-T
LAN Ports	3, 10/100 Base-T
Max. Clients	16
Recommended Clients	8
Power Supply	DC 12V/1A
Power Consumption	<12W
Operation Frequency Band	802.11a/b/g/n: 2.412 GHz to 2.472 GHz country-specific restrictions apply
Transmit Power	<20 dBm (2.4 GHz) country-specific restrictions apply
Receive Sensitivity	2.4 GHz: 802. 11b: -94 dBm (1Mbps), -81dBm (11Mbps) 802. 11g: -86 dBm (6 Mbps), -70 dBm (54 Mbps) 802. 11n (HT20): -87 dBm (MCS0), -69 dBm (MCS7) 802. 11n (HT40): -84 dBm (MCS0), -66 dBm (MCS7)
Operating Temperature	-10°C to +45°C (14 to 113 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE, RoHS

	Wireless	
Maximum Number of SSIDs	8	
Hide SSID	<b>✓</b>	
Guest Wi-Fi	<b>✓</b>	
WPA/WPA2	<b>✓</b>	
Blacklist	<b>✓</b>	
Wi-Fi Optimization	<b>✓</b>	
Transmission Power Adjustment	<b>✓</b>	
Hardware Control of the Control of t		
Flash	16 MB	
Memory	64 MB	
Color	Black	
Repeater Mode	<b>✓</b>	
WISP Mode	<b>✓</b>	
System LED Indicator	<b>✓</b>	
Power Button	-	
Reset Button	<b>✓</b>	
Power Consumption	<12W	
WAN		
Static IP	<b>✓</b>	
DHCP	<b>✓</b>	
PPPoE	<b>✓</b>	
VLAN Tag	<b>✓</b>	

	LAN	
DHCP Server	~	
Client List	<b>✓</b>	
Static IP Assignment	<b>✓</b>	
Flow Control	<b>✓</b>	
	Features	
TR069	<b>✓</b>	
IPV6	<b>✓</b>	
DDNS	<b>✓</b>	
IPTV	<b>✓</b>	
Alarm	<b>✓</b>	
Diagnosis	<b>✓</b>	
UPnP	<b>✓</b>	
ARP Binding	<b>✓</b>	
Port Mapping	<b>✓</b>	
DMZ Host	<b>✓</b>	
Rate Limitation of Terminals	<b>✓</b>	
Hardware NAT	<b>✓</b>	
MAC Cloning	<b>✓</b>	
Cloud Management	<b>✓</b>	
WISP MODE	<b>✓</b>	
Security Security		
Parental Control	Schedule	
Protect TCP Flood Attacks	<b>✓</b>	

System	
Default IP Address	192.168.110.1
URL Access	<b>✓</b>
Local Upgrade	<b>✓</b>
Online Upgrade	<b>✓</b>
APP Upgrade	<b>✓</b>
Syslog	<b>✓</b>
Backup	<b>✓</b>
Factory Reset	<b>✓</b>

# **/** Package Contents

Wireless Router	RG-EW300 PRO
Power Adapter	1
Quick Start Guide	1
UTP Cable	Cat5e
Package Weight	0.32 kg

Package Dimension (w×d×h)

329 mm × 230 mm × 55 mm





#### Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

#### Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd.
Website: https://reyee.ruijie.com/en-global