



CORD SPECIFICATION

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE : 2~10 OHMS MAX. INSULATOR RESISTANCE: 5M OHMS MIN.
3. HI-POT: DC 300V 0.01sec.
4. ALL MATERIAL FIT ROHS STANDARD (INCLUDE ALL PACKING OR OTHER MATERIAL).

Shenzhen Baixunhui Technolody Co.,Ltd.

NO.	SPECIFICATION STANDARD	QTY
①	RJ45 SHIELDED MALE CONNECTOR, SHORT TYPE, PIN GOLD PLATED Fu".	2pcs
②	CAT6A U/FTP CABLE 32AWG(7/0.08BC)*4P, OD: Ø7.2*2.2±0.15MM, LSZH JACKET COLOR: GRAY	1pcs
	3. MOLD PVC GRAY	2pcs

DESCRIPTION:	CAT6A -FTP-32AWG-XXM		NO.		
P/N ON.	CAT6A Flat Cable		PAGE:	1 OF 1	
DRAWN BY:	Alex	UNIT:	mm	SCALE:	NONE
CHECKED BY:	Yi Li	DATE:	2026.02.26	TOLER:	±0.20
APPVL BY:	ZHL			REV:	1.0

1.0	DRAWING ISSUE	2026.02.26
REV	DESCRIPTION	DATE