


AX2X8-50		DATE: Oct 10, 2014				
Cross Section		Performance				
		Electrical Characteristics:				
Marking Per request		Frequency (MHz)	Return loss (Min dB)	Attenuation Max (dB/100m)	NEXT (Min dB)	
		0.772	19.4	1.8	67.0	
		1	20.0	2.0	65.3	
		4	23.0	4.1	56.3	
		8	24.5	5.8	51.8	
		10	25.0	6.5	50.3	
		16	25.0	8.2	47.3	
		20	25.0	9.3	45.8	
		25	24.3	10.4	44.3	
		31.25	23.6	11.7	42.9	
Description Rated Temperature (°C) 75 Product Standard Certification Application Horizontal Wiring in LAN Reference Standard UL Subject 444, EIA/TIA568 & ISO/IEC 11801 Construction Conductor Solid Bare Copper AWG 24 Conductor Dia. (mm) 0.5 Insulation PE Average Thickness(mm) 0.205 Min. Point Thickness(mm) 0.198 Insulation Dia.(±0.01mm) 0.91 Twisted Pair Dia.(±0.02mm) 1.82 Assembly Dia.(±0.2mm) 3.9 Jacket PVC or LSOH Average Thickness(mm) 0.55 Min. Point Thickness(mm) 0.5 Outer Dia.(±0.2mm) 5.10 Rip Cord Per request		62.5	21.5	17.0	38.4	
		100	20.1	22.0	35.3	
		Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (Min dB/100m)	PSELFEXT (Min dB/100m)	Delay (Max ns/100m)
		0.772	64.0	66.0	63.0	575.0
		1	62.3	63.8	60.8	570.0
		4	53.3	51.7	48.7	552.0
		8	48.8	45.7	42.7	546.7
		10	47.3	43.8	40.8	545.4
		16	44.3	39.7	36.7	543.0
		20	42.8	37.7	34.7	542.0
Marking Per request		25	41.3	35.8	32.8	541.2
		31.25	39.9	33.9	30.9	540.4
		62.5	35.4	27.8	24.8	538.6
		100	32.3	23.8	20.8	537.6
		1.0-100.0MHz Impedance (ohms)				100 ± 15
		1.0-100.0MHz Delay Skew (ns/100m)				<=45
		Pair-to-Ground Capacitance Unbalance (pF/100m)				<=330
		Max. Conductor DC Resistance 20°C (ohms/km)				93.8
		Resistance Unbalance (%)				<=5
		Mechanical Characteristics:				
Test Object		Jacket				
Test Material		PVC				
Before	Tensile Strength (Mpa)	>=13.8				
Aging	Elongation (%)	>=100				
Aging Condition (°C×hrs)		100×168				
After	Tensile Strength (Mpa)	>=85% of unaged				
Aging	Elongation (%)	>=50% of unaged				
Cold Bend(-20±2°C×4hrs)		No crack				