Cabinets&Racks

General description:

Strong and stable framework of cabinet, which has the mounting holes; • The side panel and rear panel are the double-panel designed, the panels are fixed by the bolt from the inner; Between the inside and outside side panel has the inter space (spacing 25mm), which provides the channel to ventilate and support the enclosure internal heat exchange, and also can reduce the influence of the sunlight illumination; The roof panel has the awning all around stretches out 25mm and high 75mm to keep from the rain, the awning have the integrity well ventilated, which guarantees the air exchange; Luxury lock with three points bolted on the front door, side panels and rear panels are fixed by screws; The bottom can sealed with 3 sectional panels or one sectional panel; The enclosure is the 19" structure, also can install the mounting panel; The top loaded with 6 fans to ventilate, two sides have the blind holes to output heat;



S/N	LE-DA
Standard	Comply with EN60529/10.91,
Material	All Material are high-quality Sl Thickness:2.0mm
Degree of protection	IP65
Surface finish	Degreasing , Pickling , Phosp Mounting panel: color RAL200 Body of enclosure, frame, side
Size	Customized

Outdoor cabinets





IEC 60529 and GB4208-93 standard,

PCC cold rolled s teel

phating, Powder Coated, Static Powdered panel and doors: Color RAL7035CN



NINGBO LATITUDE COMMUNICATION EQUIPMENT CO., LTD