



4Pairs Outdoor Cat5e FTP Cable with messenger Specification

AX3X6 50	DATE: Oct 10, 2014																																																																																																																																																																																																																
<div style="text-align: center; border: 1px solid black; padding: 5px; margin-bottom: 10px;"> Cross Section </div> <div style="text-align: center; border: 1px solid black; padding: 5px; margin-bottom: 10px;"> Marking </div> <div style="text-align: center; border: 1px solid black; padding: 5px; margin-bottom: 10px;"> Description </div> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Rated Temperature (°C)</td> <td style="text-align: right;">75</td> </tr> <tr> <td>Product Standard Certification</td> <td></td> </tr> <tr> <td colspan="2">Application</td> </tr> <tr> <td colspan="2">Horizontal Wiring in LAN</td> </tr> <tr> <td colspan="2">Reference Standard</td> </tr> <tr> <td colspan="2">UL Subject 444, EIA/TIA568 & ISO/IEC 11801</td> </tr> <tr> <td colspan="2" style="text-align: center;">Construction</td> </tr> <tr> <td>Conductor</td> <td style="text-align: right;">Solid Bare Copper</td> </tr> <tr> <td>AWG</td> <td style="text-align: right;">24</td> </tr> <tr> <td>Conductor Dia. (mm)</td> <td style="text-align: right;">0.5</td> </tr> <tr> <td>Insulation</td> <td style="text-align: right;">PE</td> </tr> <tr> <td>Average Thickness(mm)</td> <td style="text-align: right;">0.228</td> </tr> <tr> <td>Min. Point Thickness(mm)</td> <td style="text-align: right;">0.205</td> </tr> <tr> <td>Insulation Dia.(±0.01mm)</td> <td style="text-align: right;">0.97</td> </tr> <tr> <td>Twisted Pair Dia.(±0.02mm)</td> <td style="text-align: right;">1.94</td> </tr> <tr> <td>PE-Tape(mm)</td> <td style="text-align: right;">Yes</td> </tr> <tr> <td>Drain wire (Solid Tinned Copper) Dia.(±0.003mm)</td> <td style="text-align: right;">0.40</td> </tr> <tr> <td>Al Foil Shield(mm)</td> <td style="text-align: right;">Yes</td> </tr> <tr> <td>PE-Tape(mm)</td> <td style="text-align: right;">Yes</td> </tr> <tr> <td>Assembly Dia.(±0.2mm)</td> <td style="text-align: right;">4.95</td> </tr> <tr> <td>Jacket</td> <td style="text-align: right;">LLDPE</td> </tr> <tr> <td>Average Thickness(mm)</td> <td style="text-align: right;">0.60</td> </tr> <tr> <td>Min. Point Thickness(mm)</td> <td style="text-align: right;">0.54</td> </tr> <tr> <td>Outer Dia.(±0.2mm)</td> <td style="text-align: right;">6.15</td> </tr> <tr> <td>Rip Cord</td> <td style="text-align: right;">Per request</td> </tr> <tr> <td>Self-Support wire dia(mm)</td> <td style="text-align: right;">1.0-1.2mm Steel</td> </tr> <tr> <td>Jacket</td> <td style="text-align: right;">LLDPE</td> </tr> <tr> <td colspan="2" style="text-align: center;">Color</td> </tr> <tr> <td colspan="2">Insulation colors are:</td> </tr> <tr> <td colspan="2">Blue, White/Blue</td> </tr> <tr> <td colspan="2">Orange, White/Orange</td> </tr> <tr> <td colspan="2">Green, White/Green</td> </tr> <tr> <td colspan="2">Brown, White/Brown</td> </tr> <tr> <td colspan="2">Jacket colors:</td> </tr> <tr> <td colspan="2">Per request</td> </tr> <tr> <td colspan="2" style="text-align: center;">Marking</td> </tr> <tr> <td colspan="2" style="text-align: center;">Per request</td> </tr> </table>	Rated Temperature (°C)	75	Product Standard Certification		Application		Horizontal Wiring in LAN		Reference Standard		UL Subject 444, EIA/TIA568 & ISO/IEC 11801		Construction		Conductor	Solid Bare Copper	AWG	24	Conductor Dia. (mm)	0.5	Insulation	PE	Average Thickness(mm)	0.228	Min. Point Thickness(mm)	0.205	Insulation Dia.(±0.01mm)	0.97	Twisted Pair Dia.(±0.02mm)	1.94	PE-Tape(mm)	Yes	Drain wire (Solid Tinned Copper) Dia.(±0.003mm)	0.40	Al Foil Shield(mm)	Yes	PE-Tape(mm)	Yes	Assembly Dia.(±0.2mm)	4.95	Jacket	LLDPE	Average Thickness(mm)	0.60	Min. Point Thickness(mm)	0.54	Outer Dia.(±0.2mm)	6.15	Rip Cord	Per request	Self-Support wire dia(mm)	1.0-1.2mm Steel	Jacket	LLDPE	Color		Insulation colors are:		Blue, White/Blue		Orange, White/Orange		Green, White/Green		Brown, White/Brown		Jacket colors:		Per request		Marking		Per request		<div style="text-align: center; border: 1px solid black; padding: 5px; margin-bottom: 10px;"> Performance </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> Electrical Characteristics: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Frequency (MHz)</th> <th style="text-align: left;">Return loss (Min dB)</th> <th style="text-align: left;">Attenuation (Max dB/100m)</th> <th style="text-align: left;">NEXT (Min dB)</th> </tr> </thead> <tbody> <tr><td>0.772</td><td>19.4</td><td>1.8</td><td>67.0</td></tr> <tr><td>1</td><td>20.0</td><td>2.0</td><td>65.3</td></tr> <tr><td>4</td><td>23.0</td><td>4.1</td><td>56.3</td></tr> <tr><td>8</td><td>24.5</td><td>5.8</td><td>51.8</td></tr> <tr><td>10</td><td>25.0</td><td>6.5</td><td>50.3</td></tr> <tr><td>16</td><td>25.0</td><td>8.2</td><td>47.3</td></tr> <tr><td>20</td><td>25.0</td><td>9.3</td><td>45.8</td></tr> <tr><td>25</td><td>24.3</td><td>10.4</td><td>44.3</td></tr> <tr><td>31.25</td><td>23.6</td><td>11.7</td><td>42.9</td></tr> <tr><td>62.5</td><td>21.5</td><td>17.0</td><td>38.4</td></tr> <tr><td>100</td><td>20.1</td><td>22.0</td><td>35.3</td></tr> </tbody> </table> </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Frequency (MHz)</th> <th style="text-align: left;">PSNEXT (Min dB)</th> <th style="text-align: left;">ELFEXT (lin dB/100min)</th> <th style="text-align: left;">PSELFEXT (dB/100max)</th> <th style="text-align: left;">Delay (ns/100m)</th> </tr> </thead> <tbody> <tr><td>0.772</td><td>64.0</td><td>66.0</td><td>63.0</td><td>575.0</td></tr> <tr><td>1</td><td>62.3</td><td>63.8</td><td>60.8</td><td>570.0</td></tr> <tr><td>4</td><td>53.3</td><td>51.7</td><td>48.7</td><td>552.0</td></tr> <tr><td>8</td><td>48.8</td><td>45.7</td><td>42.7</td><td>546.7</td></tr> <tr><td>10</td><td>47.3</td><td>43.8</td><td>40.8</td><td>545.4</td></tr> <tr><td>16</td><td>44.3</td><td>39.7</td><td>36.7</td><td>543.0</td></tr> <tr><td>20</td><td>42.8</td><td>37.7</td><td>34.7</td><td>542.0</td></tr> <tr><td>25</td><td>41.3</td><td>35.8</td><td>32.8</td><td>541.2</td></tr> <tr><td>31.25</td><td>39.9</td><td>33.9</td><td>30.9</td><td>540.4</td></tr> <tr><td>62.5</td><td>35.4</td><td>27.8</td><td>24.8</td><td>538.6</td></tr> <tr><td>100</td><td>32.3</td><td>23.8</td><td>20.8</td><td>537.6</td></tr> </tbody> </table> </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">1.0-100.0MHz Impedance (ohms)</td> <td style="width: 50%; text-align: right;">100 ± 15</td> </tr> <tr> <td>1.0-100.0MHz Delay Skew (ns/100m)</td> <td style="text-align: right;">≤45</td> </tr> <tr> <td>Pair-to-Ground Capacitance Unbalance (pF/100m)</td> <td style="text-align: right;">≤330</td> </tr> <tr> <td>Max. Conductor DC Resistance 20°C (ohms/km)</td> <td style="text-align: right;">93.8</td> </tr> <tr> <td>Resistance Unbalance (%)</td> <td style="text-align: right;">≤5</td> </tr> </table> </div> <div style="border: 1px solid black; padding: 5px;"> Mechanical Characteristics: <table style="width: 100%; border-collapse: collapse;"> <tr> <td>Test Object</td> <td style="text-align: right;">Jacket</td> </tr> <tr> <td>Test Material</td> <td style="text-align: right;">PVC</td> </tr> <tr> <td>Before Tensile Strength (Mpa)</td> <td style="text-align: right;">≥13.8</td> </tr> <tr> <td>Aging Elongation (%)</td> <td style="text-align: right;">≥100</td> </tr> <tr> <td>Aging Condition (°C x hrs)</td> <td style="text-align: right;">100x168</td> </tr> <tr> <td>After Tensile Strength (Mpa)</td> <td style="text-align: right;">≥85% of unaged</td> </tr> <tr> <td>Aging Elongation (%)</td> <td style="text-align: right;">≥50% of unaged</td> </tr> <tr> <td>Cold Bend(-20±2°C x 4hrs)</td> <td style="text-align: right;">No crack</td> </tr> </table> </div>	Frequency (MHz)	Return loss (Min dB)	Attenuation (Max dB/100m)	NEXT (Min dB)	0.772	19.4	1.8	67.0	1	20.0	2.0	65.3	4	23.0	4.1	56.3	8	24.5	5.8	51.8	10	25.0	6.5	50.3	16	25.0	8.2	47.3	20	25.0	9.3	45.8	25	24.3	10.4	44.3	31.25	23.6	11.7	42.9	62.5	21.5	17.0	38.4	100	20.1	22.0	35.3	Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (lin dB/100min)	PSELFEXT (dB/100max)	Delay (ns/100m)	0.772	64.0	66.0	63.0	575.0	1	62.3	63.8	60.8	570.0	4	53.3	51.7	48.7	552.0	8	48.8	45.7	42.7	546.7	10	47.3	43.8	40.8	545.4	16	44.3	39.7	36.7	543.0	20	42.8	37.7	34.7	542.0	25	41.3	35.8	32.8	541.2	31.25	39.9	33.9	30.9	540.4	62.5	35.4	27.8	24.8	538.6	100	32.3	23.8	20.8	537.6	1.0-100.0MHz Impedance (ohms)	100 ± 15	1.0-100.0MHz Delay Skew (ns/100m)	≤45	Pair-to-Ground Capacitance Unbalance (pF/100m)	≤330	Max. Conductor DC Resistance 20°C (ohms/km)	93.8	Resistance Unbalance (%)	≤5	Test Object	Jacket	Test Material	PVC	Before Tensile Strength (Mpa)	≥13.8	Aging Elongation (%)	≥100	Aging Condition (°C x hrs)	100x168	After Tensile Strength (Mpa)	≥85% of unaged	Aging Elongation (%)	≥50% of unaged	Cold Bend(-20±2°C x 4hrs)	No crack
Rated Temperature (°C)	75																																																																																																																																																																																																																
Product Standard Certification																																																																																																																																																																																																																	
Application																																																																																																																																																																																																																	
Horizontal Wiring in LAN																																																																																																																																																																																																																	
Reference Standard																																																																																																																																																																																																																	
UL Subject 444, EIA/TIA568 & ISO/IEC 11801																																																																																																																																																																																																																	
Construction																																																																																																																																																																																																																	
Conductor	Solid Bare Copper																																																																																																																																																																																																																
AWG	24																																																																																																																																																																																																																
Conductor Dia. (mm)	0.5																																																																																																																																																																																																																
Insulation	PE																																																																																																																																																																																																																
Average Thickness(mm)	0.228																																																																																																																																																																																																																
Min. Point Thickness(mm)	0.205																																																																																																																																																																																																																
Insulation Dia.(±0.01mm)	0.97																																																																																																																																																																																																																
Twisted Pair Dia.(±0.02mm)	1.94																																																																																																																																																																																																																
PE-Tape(mm)	Yes																																																																																																																																																																																																																
Drain wire (Solid Tinned Copper) Dia.(±0.003mm)	0.40																																																																																																																																																																																																																
Al Foil Shield(mm)	Yes																																																																																																																																																																																																																
PE-Tape(mm)	Yes																																																																																																																																																																																																																
Assembly Dia.(±0.2mm)	4.95																																																																																																																																																																																																																
Jacket	LLDPE																																																																																																																																																																																																																
Average Thickness(mm)	0.60																																																																																																																																																																																																																
Min. Point Thickness(mm)	0.54																																																																																																																																																																																																																
Outer Dia.(±0.2mm)	6.15																																																																																																																																																																																																																
Rip Cord	Per request																																																																																																																																																																																																																
Self-Support wire dia(mm)	1.0-1.2mm Steel																																																																																																																																																																																																																
Jacket	LLDPE																																																																																																																																																																																																																
Color																																																																																																																																																																																																																	
Insulation colors are:																																																																																																																																																																																																																	
Blue, White/Blue																																																																																																																																																																																																																	
Orange, White/Orange																																																																																																																																																																																																																	
Green, White/Green																																																																																																																																																																																																																	
Brown, White/Brown																																																																																																																																																																																																																	
Jacket colors:																																																																																																																																																																																																																	
Per request																																																																																																																																																																																																																	
Marking																																																																																																																																																																																																																	
Per request																																																																																																																																																																																																																	
Frequency (MHz)	Return loss (Min dB)	Attenuation (Max dB/100m)	NEXT (Min dB)																																																																																																																																																																																																														
0.772	19.4	1.8	67.0																																																																																																																																																																																																														
1	20.0	2.0	65.3																																																																																																																																																																																																														
4	23.0	4.1	56.3																																																																																																																																																																																																														
8	24.5	5.8	51.8																																																																																																																																																																																																														
10	25.0	6.5	50.3																																																																																																																																																																																																														
16	25.0	8.2	47.3																																																																																																																																																																																																														
20	25.0	9.3	45.8																																																																																																																																																																																																														
25	24.3	10.4	44.3																																																																																																																																																																																																														
31.25	23.6	11.7	42.9																																																																																																																																																																																																														
62.5	21.5	17.0	38.4																																																																																																																																																																																																														
100	20.1	22.0	35.3																																																																																																																																																																																																														
Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (lin dB/100min)	PSELFEXT (dB/100max)	Delay (ns/100m)																																																																																																																																																																																																													
0.772	64.0	66.0	63.0	575.0																																																																																																																																																																																																													
1	62.3	63.8	60.8	570.0																																																																																																																																																																																																													
4	53.3	51.7	48.7	552.0																																																																																																																																																																																																													
8	48.8	45.7	42.7	546.7																																																																																																																																																																																																													
10	47.3	43.8	40.8	545.4																																																																																																																																																																																																													
16	44.3	39.7	36.7	543.0																																																																																																																																																																																																													
20	42.8	37.7	34.7	542.0																																																																																																																																																																																																													
25	41.3	35.8	32.8	541.2																																																																																																																																																																																																													
31.25	39.9	33.9	30.9	540.4																																																																																																																																																																																																													
62.5	35.4	27.8	24.8	538.6																																																																																																																																																																																																													
100	32.3	23.8	20.8	537.6																																																																																																																																																																																																													
1.0-100.0MHz Impedance (ohms)	100 ± 15																																																																																																																																																																																																																
1.0-100.0MHz Delay Skew (ns/100m)	≤45																																																																																																																																																																																																																
Pair-to-Ground Capacitance Unbalance (pF/100m)	≤330																																																																																																																																																																																																																
Max. Conductor DC Resistance 20°C (ohms/km)	93.8																																																																																																																																																																																																																
Resistance Unbalance (%)	≤5																																																																																																																																																																																																																
Test Object	Jacket																																																																																																																																																																																																																
Test Material	PVC																																																																																																																																																																																																																
Before Tensile Strength (Mpa)	≥13.8																																																																																																																																																																																																																
Aging Elongation (%)	≥100																																																																																																																																																																																																																
Aging Condition (°C x hrs)	100x168																																																																																																																																																																																																																
After Tensile Strength (Mpa)	≥85% of unaged																																																																																																																																																																																																																
Aging Elongation (%)	≥50% of unaged																																																																																																																																																																																																																
Cold Bend(-20±2°C x 4hrs)	No crack																																																																																																																																																																																																																