# Cabinets&Racks

## General description:

- Vented front and rear door with excellent ventilation rate above 70%;
- Removable side panels with lock optional;
- Adjustable cable entry on the top and bottom cover;
- Welded steel frame for front and back part, flat packing is available;
- S-shaped mounting profile, free to move forward and back;
- Various optional accessories for common using;





Front

Rear

S/N	LE-ND
Standard	Comply with ANS/EIA RS-310-D
Material	SPCC quality cold rolled steel; Mounting profile:thickness:2.0
Loading Capacity	Static loading: 800kg (on the
Degree of protection	IP20
Surface finish	Degreasing, Pickling, Phosp
Product specification	18U-47U Width: 600mm, 800mm Depth: 600mm, 800mm, 9

### Server cabinets



IEC297-2, DIN41491, PART1, DIN41491, PART7, ETSI Standard;

0mm; Others:1.2mm; adjustable feet) phating, Powder Coated 900mm, 1000mm, 1200mm

# Cabinets&Racks



#### Main structure(800mm width):

- 1 Top cover
- 5 Mounting angle
- 9 Bottom panel
- 2 Fan unit
- 6 Rear door with hexagonal holes 7 High-density vented rear door 8 Steel rear door without hole
- 10 Heavy duty castor
- 13 Cable management slot 14 Front door
- 17 Front door
- 18 Front door



#### Main structure(600mm width):

- 1 Top cover
- 5 door with hexagonal holes
- 9 Heavy duty castor
- 13 Front door
- 2 Fan unit
- 6 High-density vented door
- 10 Frame
- 14 Front door

### Server cabinets



- 3 Mounting profile
- 11 Frame
- 15 Front door
- 4 Spacer
- 12 Side panel
- 16 Front door

- 3 Mounting profile
- 7 Steel rear door without hole
- 11 Side panel
- 15 Front door

- 4 Mounting angle
- Bottom panel
- 12 Front door
- 16 Front door