



NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5AMP
3. CONTACT RESISTANCE: 100MILLIOHMS MAX
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE: -40° TO +85°
2. OPERATION: 0° TO 70°

MECHANICAL:

1. HOUSING MATERIAL: ABS;
2. PANEL FRAME: CARBON STEEL, POWDER, COATING IN BLACK COLOR, Spec 1.5mm;
3. PCB MATERIAL: FR-4T=1.6mm;
4. IDC MATERIAL: PC, CONTACT: PHOSPHOR BRONZE; WITH NICKEL PLATING;
5. RJ45 JACK LIFE: 750 TIMES MIN;
6. IDC LIFE: 200 TIMES MIN;
7. WIRE: AWG22-26;

					Solarstar Electronics Industrial Co., Ltd.								
					Material				ItemNo.	SS-PP6-04			
					Angles Projection	Size	Scale	Unit	PartName	24PortsCat6UTPPatchPanel			
SYM	Number	BillNo. of Alteration	Signature	Date		A4	X:1	mm	ERP				
Drawn	Dingjianbo	2016. 1. 9	Tolerance						Sheet	10F1	Version: A/0	PartNo.	
Checked	Gepeijun	2016. 1. 9	0.00-20.00	±0.10									
			20.00-50.00	±0.15									
			50.00-100.00	±0.20									
			100.00-	±0.25									
Approved	Wangweijun	2016. 1. 9	Angle	±30'									