



- TYPE:**
1. SHIELDED CAT.6 48PORT PATCH PANEL
 2. COLOUR: BLACK
- ELECTRICAL:**
1. CONTACT RESISTANCE: 20M OHMS MAX
 2. INSULATION RESISTANCE: 500M OHMS @500V DC
 3. WITHSTAND VOLTAGE: DC1000V AC700V RMS 60HZ 1MIN
 4. CAT6 PERMANENT LINK: CONFORM TO ANSI/TIA/EIA 568B.2-10
- ENVIRONMENTAL:**
1. STORAGE: -40° $+70^{\circ}$
 2. OPERATION: -10° $+60^{\circ}$
- MECHANICAL:**
1. SHIELDED MATERIAL: COLD ROLLED PLATE
 2. IDC MATERIAL: PC UL94V-0, Accept 22-26 AWG Solid Wire
 3. TERMINAL: PHOSPHOR BRONZE, TIN GOLD 3U/6U/15U/30U/50U*
 4. RJ45 CONTACT LIFE: 750 TIMES MIN
 5. IDN LIFE: 250 TIMES MIN

Solarstar Electronics Industrial Co.,Ltd.			
	SCALE	MATERIAL	DWG NO
SHEET		TITLE	SS-3217SK48-C6
APPROVAL	CHECKED	DRAWN	