



4Pairs Cat5e UTP Outdoor Cable Specification

4N2X3 55		DATE:2014.10.10																																																													
Cross Section		Performance																																																													
		Electrical Characteristics: <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Frequency (MHz)</th> <th>Return loss (Min dB)</th> <th>Attenuation Max (dB/100m)</th> <th>NEXT (Min dB)</th> </tr> </thead> <tbody> <tr><td>0.772</td><td>19.4</td><td>1.8</td><td>67.0</td></tr> <tr><td>1</td><td>20.0</td><td>2.0</td><td>65.3</td></tr> <tr><td>4</td><td>23.0</td><td>4.1</td><td>56.3</td></tr> <tr><td>8</td><td>24.5</td><td>5.8</td><td>51.8</td></tr> <tr><td>10</td><td>25.0</td><td>6.5</td><td>50.3</td></tr> <tr><td>16</td><td>25.0</td><td>8.2</td><td>47.3</td></tr> <tr><td>20</td><td>25.0</td><td>9.3</td><td>45.8</td></tr> <tr><td>25</td><td>24.3</td><td>10.4</td><td>44.3</td></tr> <tr><td>31.25</td><td>23.6</td><td>11.7</td><td>42.9</td></tr> <tr><td>62.5</td><td>21.5</td><td>17.0</td><td>38.4</td></tr> <tr><td>100</td><td>20.1</td><td>22.0</td><td>35.3</td></tr> </tbody> </table>		Frequency (MHz)	Return loss (Min dB)	Attenuation Max (dB/100m)	NEXT (Min dB)	0.772	19.4	1.8	67.0	1	20.0	2.0	65.3	4	23.0	4.1	56.3	8	24.5	5.8	51.8	10	25.0	6.5	50.3	16	25.0	8.2	47.3	20	25.0	9.3	45.8	25	24.3	10.4	44.3	31.25	23.6	11.7	42.9	62.5	21.5	17.0	38.4	100	20.1	22.0	35.3												
Frequency (MHz)	Return loss (Min dB)	Attenuation Max (dB/100m)	NEXT (Min dB)																																																												
0.772	19.4	1.8	67.0																																																												
1	20.0	2.0	65.3																																																												
4	23.0	4.1	56.3																																																												
8	24.5	5.8	51.8																																																												
10	25.0	6.5	50.3																																																												
16	25.0	8.2	47.3																																																												
20	25.0	9.3	45.8																																																												
25	24.3	10.4	44.3																																																												
31.25	23.6	11.7	42.9																																																												
62.5	21.5	17.0	38.4																																																												
100	20.1	22.0	35.3																																																												
Marking		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Frequency (MHz)</th> <th>PSNEXT (Min dB)</th> <th>ELFEXT (Min dB/100m)</th> <th>PSELFEXT (Min dB/100m)</th> <th>Delay (ns/100m)</th> </tr> </thead> <tbody> <tr><td>0.772</td><td>64.0</td><td>66.0</td><td>63.0</td><td>575.0</td></tr> <tr><td>1</td><td>62.3</td><td>63.8</td><td>60.8</td><td>570.0</td></tr> <tr><td>4</td><td>53.3</td><td>51.7</td><td>48.7</td><td>552.0</td></tr> <tr><td>8</td><td>48.8</td><td>45.7</td><td>42.7</td><td>546.7</td></tr> <tr><td>10</td><td>47.3</td><td>43.8</td><td>40.8</td><td>545.4</td></tr> <tr><td>16</td><td>44.3</td><td>39.7</td><td>36.7</td><td>543.0</td></tr> <tr><td>20</td><td>42.8</td><td>37.7</td><td>34.7</td><td>542.0</td></tr> <tr><td>25</td><td>41.3</td><td>35.8</td><td>32.8</td><td>541.2</td></tr> <tr><td>31.25</td><td>39.9</td><td>33.9</td><td>30.9</td><td>540.4</td></tr> <tr><td>62.5</td><td>35.4</td><td>27.8</td><td>24.8</td><td>538.6</td></tr> <tr><td>100</td><td>32.3</td><td>23.8</td><td>20.8</td><td>537.6</td></tr> </tbody> </table>		Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (Min dB/100m)	PSELFEXT (Min dB/100m)	Delay (ns/100m)	0.772	64.0	66.0	63.0	575.0	1	62.3	63.8	60.8	570.0	4	53.3	51.7	48.7	552.0	8	48.8	45.7	42.7	546.7	10	47.3	43.8	40.8	545.4	16	44.3	39.7	36.7	543.0	20	42.8	37.7	34.7	542.0	25	41.3	35.8	32.8	541.2	31.25	39.9	33.9	30.9	540.4	62.5	35.4	27.8	24.8	538.6	100	32.3	23.8	20.8	537.6
Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (Min dB/100m)	PSELFEXT (Min dB/100m)	Delay (ns/100m)																																																											
0.772	64.0	66.0	63.0	575.0																																																											
1	62.3	63.8	60.8	570.0																																																											
4	53.3	51.7	48.7	552.0																																																											
8	48.8	45.7	42.7	546.7																																																											
10	47.3	43.8	40.8	545.4																																																											
16	44.3	39.7	36.7	543.0																																																											
20	42.8	37.7	34.7	542.0																																																											
25	41.3	35.8	32.8	541.2																																																											
31.25	39.9	33.9	30.9	540.4																																																											
62.5	35.4	27.8	24.8	538.6																																																											
100	32.3	23.8	20.8	537.6																																																											
Description		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>Rated Temperature (°C)</td> <td style="text-align: right;">75</td> </tr> <tr> <td>Product Standard Certification</td> <td></td> </tr> <tr> <td colspan="2">Application</td> </tr> <tr> <td colspan="2">Horizontal Wiring in LAN</td> </tr> <tr> <td colspan="2">Reference Standard</td> </tr> <tr> <td colspan="2">UL Subject 444,EIA/TIA568 & ISO/IEC 11801</td> </tr> </tbody> </table>		Rated Temperature (°C)	75	Product Standard Certification		Application		Horizontal Wiring in LAN		Reference Standard		UL Subject 444,EIA/TIA568 & ISO/IEC 11801																																																	
Rated Temperature (°C)	75																																																														
Product Standard Certification																																																															
Application																																																															
Horizontal Wiring in LAN																																																															
Reference Standard																																																															
UL Subject 444,EIA/TIA568 & ISO/IEC 11801																																																															
Construction		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>Conductor</td> <td style="text-align: right;">Solid Bare Copper</td> </tr> <tr> <td>AWG</td> <td style="text-align: right;">24</td> </tr> <tr> <td>Conductor Dia. (mm)</td> <td style="text-align: right;">0.5</td> </tr> <tr> <td>Insulation</td> <td style="text-align: right;">PE</td> </tr> <tr> <td>Average Thickness(mm)</td> <td style="text-align: right;">0.205</td> </tr> <tr> <td>Min. Point Thickness(mm)</td> <td style="text-align: right;">0.198</td> </tr> <tr> <td>Insulation Dia.(±0.01mm)</td> <td style="text-align: right;">0.91</td> </tr> <tr> <td>Twisted Pair Dia.(±0.02mm)</td> <td style="text-align: right;">1.82</td> </tr> <tr> <td>Assembly Dia.(±0.2mm)</td> <td style="text-align: right;">3.9</td> </tr> <tr> <td colspan="2">Jacket</td> </tr> <tr> <td colspan="2" style="text-align: right;">LLDPE</td> </tr> <tr> <td>Average Thickness(mm)</td> <td style="text-align: right;">0.55</td> </tr> <tr> <td>Min. Point Thickness(mm)</td> <td style="text-align: right;">0.5</td> </tr> <tr> <td>Outer Dia.(±0.2mm)</td> <td style="text-align: right;">5.10</td> </tr> <tr> <td>Rip Cord</td> <td style="text-align: right;">Per request</td> </tr> </tbody> </table>		Conductor	Solid Bare Copper	AWG	24	Conductor Dia. (mm)	0.5	Insulation	PE	Average Thickness(mm)	0.205	Min. Point Thickness(mm)	0.198	Insulation Dia.(±0.01mm)	0.91	Twisted Pair Dia.(±0.02mm)	1.82	Assembly Dia.(±0.2mm)	3.9	Jacket		LLDPE		Average Thickness(mm)	0.55	Min. Point Thickness(mm)	0.5	Outer Dia.(±0.2mm)	5.10	Rip Cord	Per request																														
Conductor	Solid Bare Copper																																																														
AWG	24																																																														
Conductor Dia. (mm)	0.5																																																														
Insulation	PE																																																														
Average Thickness(mm)	0.205																																																														
Min. Point Thickness(mm)	0.198																																																														
Insulation Dia.(±0.01mm)	0.91																																																														
Twisted Pair Dia.(±0.02mm)	1.82																																																														
Assembly Dia.(±0.2mm)	3.9																																																														
Jacket																																																															
LLDPE																																																															
Average Thickness(mm)	0.55																																																														
Min. Point Thickness(mm)	0.5																																																														
Outer Dia.(±0.2mm)	5.10																																																														
Rip Cord	Per request																																																														
Color		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td colspan="2">Insulation colors are:</td> </tr> <tr> <td colspan="2">Blue,White/Blue</td> </tr> <tr> <td colspan="2">Orange,White/Orange</td> </tr> <tr> <td colspan="2">Green,White/Green</td> </tr> <tr> <td colspan="2">Brown,White/Brown</td> </tr> <tr> <td colspan="2">Jacket colors:</td> </tr> <tr> <td colspan="2">Per request</td> </tr> </tbody> </table>		Insulation colors are:		Blue,White/Blue		Orange,White/Orange		Green,White/Green		Brown,White/Brown		Jacket colors:		Per request																																															
Insulation colors are:																																																															
Blue,White/Blue																																																															
Orange,White/Orange																																																															
Green,White/Green																																																															
Brown,White/Brown																																																															
Jacket colors:																																																															
Per request																																																															
Marking		Mechanical Characteristics: <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>Test Object</td> <td>Jacket</td> </tr> <tr> <td>Test Material</td> <td>PVC</td> </tr> <tr> <td>Before Tensile Strength (Mpa)</td> <td style="text-align: right;">>=13.8</td> </tr> <tr> <td>Aging Elongation (%)</td> <td style="text-align: right;">>=100</td> </tr> <tr> <td>Aging Condition (°Cxhrs)</td> <td style="text-align: right;">100x168</td> </tr> <tr> <td>After Tensile Strength (Mpa)</td> <td style="text-align: right;">>=85% of unaged</td> </tr> <tr> <td>Aging Elongation (%)</td> <td style="text-align: right;">>=50% of unaged</td> </tr> <tr> <td>Cold Bend(-20±2°Cx4hrs)</td> <td style="text-align: right;">No crack</td> </tr> </tbody> </table>		Test Object	Jacket	Test Material	PVC	Before Tensile Strength (Mpa)	>=13.8	Aging Elongation (%)	>=100	Aging Condition (°Cxhrs)	100x168	After Tensile Strength (Mpa)	>=85% of unaged	Aging Elongation (%)	>=50% of unaged	Cold Bend(-20±2°Cx4hrs)	No crack																																												
Test Object	Jacket																																																														
Test Material	PVC																																																														
Before Tensile Strength (Mpa)	>=13.8																																																														
Aging Elongation (%)	>=100																																																														
Aging Condition (°Cxhrs)	100x168																																																														
After Tensile Strength (Mpa)	>=85% of unaged																																																														
Aging Elongation (%)	>=50% of unaged																																																														
Cold Bend(-20±2°Cx4hrs)	No crack																																																														