

4X2X0.57		DATE: Oct 10, 2014																																																																		
<b>Cross Section</b>		<b>Performance</b>																																																																		
		<b>Electrical Characteristics:</b> <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>Return loss (Min dB)</th> <th>Attenuation Max (dB/100m)</th> <th>NEXT (Min dB)</th> </tr> </thead> <tbody> <tr><td>1</td><td>20.0</td><td>2.0</td><td>65.3</td></tr> <tr><td>4</td><td>23.0</td><td>4.1</td><td>56.3</td></tr> <tr><td>8</td><td>24.5</td><td>5.8</td><td>51.8</td></tr> <tr><td>16</td><td>26.0</td><td>8.2</td><td>47.3</td></tr> <tr><td>20</td><td>26.5</td><td>9.3</td><td>45.8</td></tr> <tr><td>62.5</td><td>25.0</td><td>17.0</td><td>38.4</td></tr> <tr><td>100</td><td>25.0</td><td>22.0</td><td>35.3</td></tr> <tr><td>200</td><td>18.0</td><td>32.4</td><td>30.8</td></tr> <tr><td>250</td><td>17.3</td><td>36.9</td><td>29.3</td></tr> <tr><td>300</td><td>16.8</td><td>41.0</td><td>28.2</td></tr> <tr><td>400</td><td>15.9</td><td>48.5</td><td>26.3</td></tr> <tr><td>500</td><td>15.2</td><td>55.5</td><td>24.8</td></tr> </tbody> </table>		Frequency (MHz)	Return loss (Min dB)	Attenuation Max (dB/100m)	NEXT (Min dB)	1	20.0	2.0	65.3	4	23.0	4.1	56.3	8	24.5	5.8	51.8	16	26.0	8.2	47.3	20	26.5	9.3	45.8	62.5	25.0	17.0	38.4	100	25.0	22.0	35.3	200	18.0	32.4	30.8	250	17.3	36.9	29.3	300	16.8	41.0	28.2	400	15.9	48.5	26.3	500	15.2	55.5	24.8													
Frequency (MHz)	Return loss (Min dB)	Attenuation Max (dB/100m)	NEXT (Min dB)																																																																	
1	20.0	2.0	65.3																																																																	
4	23.0	4.1	56.3																																																																	
8	24.5	5.8	51.8																																																																	
16	26.0	8.2	47.3																																																																	
20	26.5	9.3	45.8																																																																	
62.5	25.0	17.0	38.4																																																																	
100	25.0	22.0	35.3																																																																	
200	18.0	32.4	30.8																																																																	
250	17.3	36.9	29.3																																																																	
300	16.8	41.0	28.2																																																																	
400	15.9	48.5	26.3																																																																	
500	15.2	55.5	24.8																																																																	
<b>Marking</b>		<table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>PSNEXT (Min dB)</th> <th>ELFEXT (Min (dB/100m))</th> <th>PSELFEXT (Min (dB/100m))</th> <th>Delay (ns/100m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>62.3</td><td>63.8</td><td>60.8</td><td>570.0</td></tr> <tr><td>4</td><td>53.3</td><td>51.7</td><td>48.7</td><td>552.0</td></tr> <tr><td>8</td><td>48.8</td><td>45.7</td><td>42.7</td><td>546.7</td></tr> <tr><td>16</td><td>44.3</td><td>39.7</td><td>36.7</td><td>543.0</td></tr> <tr><td>20</td><td>42.8</td><td>37.7</td><td>34.7</td><td>542.0</td></tr> <tr><td>62.5</td><td>35.4</td><td>27.8</td><td>24.8</td><td>538.6</td></tr> <tr><td>100</td><td>32.3</td><td>23.8</td><td>20.8</td><td>537.6</td></tr> <tr><td>200</td><td>27.8</td><td>17.7</td><td>14.7</td><td>536.5</td></tr> <tr><td>250</td><td>26.3</td><td>15.8</td><td>12.8</td><td>536.3</td></tr> <tr><td>300</td><td>25.2</td><td>14.2</td><td>11.2</td><td>536.1</td></tr> <tr><td>400</td><td>23.3</td><td>11.7</td><td>8.7</td><td>535.8</td></tr> <tr><td>500</td><td>21.8</td><td>9.8</td><td>6.8</td><td>535.6</td></tr> </tbody> </table>		Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (Min (dB/100m))	PSELFEXT (Min (dB/100m))	Delay (ns/100m)	1	62.3	63.8	60.8	570.0	4	53.3	51.7	48.7	552.0	8	48.8	45.7	42.7	546.7	16	44.3	39.7	36.7	543.0	20	42.8	37.7	34.7	542.0	62.5	35.4	27.8	24.8	538.6	100	32.3	23.8	20.8	537.6	200	27.8	17.7	14.7	536.5	250	26.3	15.8	12.8	536.3	300	25.2	14.2	11.2	536.1	400	23.3	11.7	8.7	535.8	500	21.8	9.8	6.8	535.6
Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (Min (dB/100m))	PSELFEXT (Min (dB/100m))	Delay (ns/100m)																																																																
1	62.3	63.8	60.8	570.0																																																																
4	53.3	51.7	48.7	552.0																																																																
8	48.8	45.7	42.7	546.7																																																																
16	44.3	39.7	36.7	543.0																																																																
20	42.8	37.7	34.7	542.0																																																																
62.5	35.4	27.8	24.8	538.6																																																																
100	32.3	23.8	20.8	537.6																																																																
200	27.8	17.7	14.7	536.5																																																																
250	26.3	15.8	12.8	536.3																																																																
300	25.2	14.2	11.2	536.1																																																																
400	23.3	11.7	8.7	535.8																																																																
500	21.8	9.8	6.8	535.6																																																																
Per request		<table border="1"> <tbody> <tr> <td>1.0-100.0MHz Impedance (ohms)</td> <td>100 ± 15</td> </tr> <tr> <td>1.0-100.0MHz Delay Skew (ns/100m)</td> <td>&lt;=45</td> </tr> <tr> <td>Pair-to-Ground Capacitance Unbalance (pF/100m)</td> <td>&lt;=330</td> </tr> <tr> <td>Max. Conductor DC Resistance 20°C (ohms/km)</td> <td>72.2</td> </tr> <tr> <td>Resistance Unbalance (%)</td> <td>&lt;=5</td> </tr> </tbody> </table>		1.0-100.0MHz Impedance (ohms)	100 ± 15	1.0-100.0MHz Delay Skew (ns/100m)	<=45	Pair-to-Ground Capacitance Unbalance (pF/100m)	<=330	Max. Conductor DC Resistance 20°C (ohms/km)	72.2	Resistance Unbalance (%)	<=5																																																							
1.0-100.0MHz Impedance (ohms)	100 ± 15																																																																			
1.0-100.0MHz Delay Skew (ns/100m)	<=45																																																																			
Pair-to-Ground Capacitance Unbalance (pF/100m)	<=330																																																																			
Max. Conductor DC Resistance 20°C (ohms/km)	72.2																																																																			
Resistance Unbalance (%)	<=5																																																																			
<b>Description</b>		<b>Mechanical Characteristics:</b>																																																																		
Rated Temperature (°C)	75	Test Object	Jacket																																																																	
<b>Application</b>		Test Material	LSZH/PVC																																																																	
Horizontal Wiring in LAN		Before Tensile Strength (Mpa)	>=13.8																																																																	
<b>Reference Standard</b>		Aging Elongation (%)	>=100																																																																	
UL Subject 444,EIA/TIA568 & ISO/IEC 11801		Aging Condition (°Cxhrs)	100x168																																																																	
<b>Construction</b>		After Tensile Strength (Mpa)	>=85% of unaged																																																																	
Conductor	Solid Bare Copper	Aging Elongation (%)	>=50% of unaged																																																																	
AWG	23	Cold Bend(-20±2°Cx4hrs)	No crack																																																																	
Conductor Dia. (±0.05mmmm)	0.57																																																																			
Insulation	PE																																																																			
Average Thickness(mm)	0.220																																																																			
Min. Point Thickness(mm)	0.200																																																																			
Insulation Dia.(±0.01mm)	1.01																																																																			
Twisted Pair Dia.(±0.02mm)	2.02																																																																			
Filler	PE/PVC																																																																			
Assembly Dia.(±0.2mm)	4.8																																																																			
Jacket	LSOH/PVC																																																																			
Average Thickness(mm)	0.60																																																																			
Min. Point Thickness(mm)	0.55																																																																			
Outer Dia.(±0.1mm)	6.30																																																																			
Rip Cord	Nylon																																																																			
<b>Color</b>																																																																				
<b>Insulation colors are:</b>																																																																				
Blue,White/Blue																																																																				
Orange,White/Orange																																																																				
Green,White/Green																																																																				
Brown,White/Brown																																																																				
<b>Jacket colors:</b>																																																																				
Per request																																																																				