

J9773A Datasheet

Get a Quote



Overview

Aruba 2530 Series Gigabit Ethernet devices are enterprise class, fully managed, Layer 2 edge switches delivering cost effective, reliable, and secure connectivity for business networks. Designed for entry level to midsize enterprise networks, these Gigabit Ethernet switches deliver full Layer 2 capabilities with enhanced access security, traffic prioritization, IPv6 host support, and optional PoE+. The 2530 24G PoE+ model has 24 x 10/100/1000 PoE enabled ports and four Gigabit SFP ports.

Quick Spec

Table 1 shows the quick spec.

Product Code	J9773A
Type	Aruba 2530-24G-PoE+ Switch
Ports	· 24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only · 4 fixed Gigabit Ethernet SFP ports · 1 dual-personality (RJ-45 or USB micro-B) serial console port.
PoE power	195 W
Throughput	up to 41.6 million pps (64-byte packets)
Switching capacity	56 Gb/s
Dimensions (W x D x H)	44.3 x 33.02 x 4.45 cm (17.44 x 13.00 x 1.75 in) (1U height)
Weight	3.95 kg (8.7 lb)

Product Details

Figure 1 shows the appearance of Aruba J9773A.



Figure 2 shows the back panel of Aruba J9773A.



Note:

(1)	AC Power Connector
-----	--------------------

Compare to Similar Items

Table 2 shows the comparison.

Product Code	J9783A	J9776A	J9775A	J9773A	J9772A
Type	Aruba 2530-8 Switch	Aruba 2530-24G Switch	Aruba 2530-48G Switch	Aruba 2530-24G-PoE+ Switch	Aruba 2530-48G-PoE+ Switch
PoE power	N/A	N/A	N/A	195 W	382 W
Throughput	up to 4.1 million pps (64-byte packets)	Up to 41.6 million pps (64-byte packets)	Up to 77.3 Mp/s (64-byte packets)	up to 41.6 million pps (64-byte packets)	Up to 77.3 million pps (64-byte packets)
Switching capacity	5.6 Gb/s	56 Gb/s	104 Gb/s	56 Gb/s	104 Gb/s

Get more information

Do you have any question about the J9773A?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

J9773A Specifications	
Type	Aruba 2530-24G-PoE+ Switch
System specifications	
Ports	· 24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only · 4 fixed Gigabit Ethernet SFP ports · 1 dual-personality (RJ-45 or USB micro-B) serial console port.
Memory and processor	Processor: ARM9E @ 800 MHz, 128 MB flash, 256 MB DDR3 DIMM; packet buffer size: 1.5 MB dynamically allocated.
Mounting	Mounts in an EIA-standard 19-inch telco rack or equipment cabinet (rack-mounting kit available); horizontal surface mounting; wall mounting.

Management	IMC - Intelligent Management Center; Command-Line Interface (CLI); Web browser; configuration menu; out-of-band management (serial RS-232C or Micro USB);IEEE 802.3 Ethernet MIB; Repeater MIB; Ethernet Interface MIB.
Performance (IPv6 Ready Certified)	
1000 Mb latency	< 2.3 μs (LIFO 64-byte packets)
100 Mb Latency	< 7.4 μs (LIFO 64-byte packets)
Throughput	up to 41.6 million pps (64-byte packets)
Switching capacity	56 Gb/s
MAC address table size	16000 entries
Physical specifications	
Dimensions (W x D x H)	44.3 x 33.02 x 4.45 cm (17.44 x 13.00 x 1.75 in) (1U height)
Weight	3.95 kg (8.7 lb)
Electrical specifications	
Maximum heat dissipation	135 BTU/hr (142.42 kJ/hr), (switch only: 135 BTU/hr; combined switch + max. PoE devices: 843 BTU/hr)
Voltage	100 - 127 / 200 - 240 V ac
Current	3.2/1.6 A
Idle power1	25.2 W
Maximum power rating2	247 W
PoE power	195 W
Frequency	50/60 Hz
NOTE: 1: Idle power is the actual power consumption of the device with no ports connected. 2: Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the total power budget available to all PoE ports.	
Environmental specifications	
Operating temperature	0° to 45°C (32° to 113°F)
Operating relative humidity	15% to 95% @ 40°C (104°F), noncondensing
Non-operating/storage temperature	-40° to 70°C (-40° to 158°F)
Non-operating/storage relative humidity	15% to 90% @ 65°C (149°F), noncondensing
Altitude	Up to 3 km (10,000 ft)
Acoustic	Power: 39.6 dB, Pressure: 43.9 dB
Safety agency certifications	
Safety	UL 60950-1; CAN/CSA 22.2 No. 60950-1; EN 60825; IEC 60950-1; EN 60950-1

NOTE: IEEE 802.3az applies to Gigabit models only; IEEE 802.3at and IEEE 802.3af apply to PoE+ models only. When using SFPs with this product, SFPs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required.

Want to Buy

[Order Now](#)[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com