



# UC510 IP Office for SOHO



UC510 is specially designed as IP Office for SOHOs (Small Office and Home Offices). The new solution offers not only a Wi-Fi router supporting VPN Client/Server, external ADSL, ... but also a fully featured IP PBX that can host up to 10 extensions with 2 analog ports connected (PSTN line (FXO)/ analog phone (FXS)); and supports Call Forward, Blind/Attendant Transfer and so on.

UC510 is configured and managed through a single web GUI which significantly reduces the time and effort required to install the product. This simplified management and reduction in hardware costs through merging two products into one makes the UC510 an amazing and cost effective solution for SOHOs.

## System Specifications

### IP PBX Features

#### Extensions

10 Extensions  
Batch-Add Extensions  
UDP/TCP Transport  
SIP/IAX/FXO Trunks

#### Outbound Routes

DialPlan  
IVR

#### Inbound Controls

Analog Port DID  
Number DID  
DOD  
IVR  
IVR Prompts  
Ring Group  
Blacklist  
Time Based Rules

#### Codecs

Audio: G.722/G.711-Ulaw/G.711-Alaw/  
G.726/G.729/GSM/SPEEX

#### DTMF

RFC2833  
SIP info  
Inband

#### Call Features

Caller ID  
Call Group  
Call Hold  
Call Waiting  
Call Transfer  
Call Forward (Always/Busy/No Answer)  
Call Pickup  
Call Parking  
Music on Hold/CRBT

#### Other Features

BLF  
Feature Codes  
Register Status  
Call Logs  
PBX Logs

### Wi-Fi Router Features

#### WAN

Static IP  
DHCP  
PPPoE

#### NAT

#### DHCP Server

#### Wi-Fi

SSID  
Frequency: 2.412GHz~2.484GHz  
Channels: 1~14  
IEEE802.11/b/g/n  
Security: WPA-PSK, WPA2-PSK  
AP Client MAC Address Filter  
WMM (Wi-Fi Multimedia)  
WPS (Wi-Fi Protected Setup): WPS-PIN, WPS-PBC

#### Networking Protocols

IEEE802.3(CSMA/CD), 802.3u, 802.1d/p/q/x,  
802.11/b/g/n (CSMA/CA), TCP/IP, SIP, IAX, RTP,  
RTCP, PPPoE, PPP, L2TP, PPTP, DHCP, ICMP, HTTP,  
SNTP, SSH, etc

#### Firewall

MAC/IP/Port Filter  
System Security: Remote Access, Ping from WAN Filter,  
Block Port Scan, Block SYN Flood,  
Stateful Packet Inspection (SPI)

#### Port Forwarding

#### DDNS

DDNS Support: dyndns.org, freedns.afraid.org  
zoneedit.com, no-ip.com

#### Static Routing

#### Troubleshooting

Ping Test, Traceroute Test

#### VPN Server

L2TP/PPTP

#### VPN Client

L2TP/PPTP

### Hardware Specifications

#### WAN Port

1x 10/100Base-TX Fast Ethernet, Auto MDI/MDIX

#### LAN Port

4x 10/100Base-TX Fast Ethernet, Auto MDI/MDIX

#### Telephony Port

UC51011: 1FXS+1FXO (Life-Line)  
UC51002: 2FXO

#### USB Port

2x USB2.0

#### Turbo Button

Reset/WPS-PBC

#### RAM

DDR2 128MB

#### Storage

256MB Onboard Flash

### Environment

Working Temperature: 0 °C ~ 40 °C

Storage Temperature: -20 °C ~ 55 °C

Humidity: 5% ~ 95% Non-Condensing

### Packings

Dimension: 258mm x 250mm x 55mm

Weight/Unit: 1kg

