

NOTES:

ELECTRICAL:


1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

MECHANICAL:

1. HOUSING MATERIAL:ABS;
2. PANEL FRAME: CARBON STEEL, POWDER, COATING IN BLACK COLOR, Spec 1.5mm;
3. PCB MATERIAL:FR-4T=1.6mm;
4. IDC MATERIAL:PC, CONTACT:PHOSPHOR BRONZE; WITH NICKEL PLATING;
5. RJ45 JACK LIFE:750 TIMES MIN;
6. IDC LIFE:200 TIMES MIN;
7. WIRE:AWG22-26;

					Solarstar Electronics industry Co.,Ltd.							
								Material	ItemNo.	SS-PP5-05		
								Angles Projection	Size	Scale	Unit	
									A4	X:1	mm	
									Sheet	10F1	Version: A/0	PartName
										ERP PartNo.		

SYM	Number	BillNo. of Alteration	Signature	Date
Drawn	Dingjianbo	2016. 1. 12		
Checked	Gepeijun	2016. 1. 12		
Approved	Wangweijun	2016. 1. 12		

Tolerance	
0.00-20.00	±0.10
20.00-50.00	±0.15
50.00-100.00	±0.20
100.00-Angle	±0.25 ±30'