

7934017 - KPPE-VP (250) 4x2x0,57 (FTP-cat.6)

Cable F/UTP cat.6 4x2x0,57 PE Outdoor

APPLICATION

PBX, V.11, X.21, ISDN, Ethernet (10Base-T), ATM-25/52/155 Mbit/s, 100VG-AnyLAN, Fast Ethernet (100BASE-TX), Token Ring 16/100 Mbit/s, Gigabit Ethernet (1000BASE-T), Firewire 100 Mbit/s, 10 Gigabit Ethernet (10GBASE-T*), ATM LAN 1,2 Gbit/s

COMPLIANCE WITH THE REQUIREMENTS

ISO/IEC 11801:2002

EN 50173-1:2002

ANSI/TIA -568-C.2

IEC 61156-5:2002

MECHANICAL CHARACTERISTICS

Temperature range:

During installation -10 °C ... +60 °C

After installation -20 °C ... +60 °C

Bending radius:

During installation ≥ 8 cable diameters

After installation ≥ 4 cable diameters

Tensile stress ≤ 85 N

DESIGN

1) Conductor: soft copper wire

Diameter: 0,57 mm ($\pm 0,005$ mm)

2) Insulation: PE

Conductor diameter: 1,15 mm

3) Pair: two conductors twisted together

Color identification of pairs:

pair 1: white-blue / blue

pair 2: white-orange / orange

pair 3: white-green / green

pair 4: white-brown / brown


4) Cross-web 4x4 mm

5) Core wrapping

6) Copper tinned contact wire $\varnothing 0,4$ mm is applied between the sheath and shield.

7) Core shield: aluminum polymer foil (metal inside)

8) Sheath: PE, nominal cable diameter: 7,1 mm



ELECTRICAL CHARACTERISTICS AT 20 °C

Parameter	Unit	Value
Capacitance	pF/m	≤ 56
Direct current resistance	Ohm/km	≤ 84
Insulation resistance	GOhm/km	≥ 5
Resistance unbalance	%	2
Signal propagation velocity	s	0,68
Propagation delay	ns/100 m	≤ 534+36/√f
Delay shift on the frequency 100 MHz	ns/100 m	≤ 30
Characteristic impedance in the frequency range of: 1-100 MHz 100-250 MHz	Ohm	100±15 100±22
Test voltage between cores, (DC, 2 s)	kV	2,5

Frequency, MHz	1	4	10	16	20	31,25	62,5	100	125	200	250
Attenuation, dB, max	2,1	3,8	6	7,6	8,5	10,8	15,5	19,9	22,5	29,1	33
NEXT, dB, min	75,3	66,3	60,3	57,3	55,8	52,8	48,3	45,3	43,8	40,8	39,3
PS NEXT, dB, min	72,3	63,3	57,3	54,3	52,8	49,8	45,3	42,3	40,8	37,8	36,3
ELFEXT, dB, min	68	56	48	44	42	38	32	28	26	22	20
PS ELFEXT, dB, min	65	53	45	41	39	35	29	25	23	19	17
RL, dB, min	20,0	23,0	25,0	25,0	25,0	23,6	21,5	20,1	19,4	18,0	17,3

IEC 61156-5, values lower than 4 MHz are given for information only

ORDER INFORMATION

P/N	Cable type	Packing	Weight, kg/km
7934017	KPPE-VP (250) 4x2x0,57 (FTP-cat.6)	plywood reel, 305/500 m	46,4