# High Density Side Access Troy Module CAN-TROY-700

#### Overview

Ultimate new design with the most advanced splice & patch system and cable management ever developed for high density applications on carrier & transmission side.

### Highlights

- Compact 3 U module
- Each U accommodates 2 fiber trays with each max. capacity of 24 fibers
- Max. capacity of the module is 144 fibers for SSF Duplex adaptors
- Modules are rear mounted for improved access
- Fiber trays and connected patchcords can slide in and out independently as a pull-out unit
- Easy side access ensures laser safety
- Special splice cassette design, which allows splicing on one side and professional cable storage on the other side no cable congestion!
- Cassettes are tiltable up to 135 degree for ease of installation
  and maintenance
- Special incoming cable fixing unit which ensures strong, easy and quick cable fixing for miniflex tubes no need to use time consuming plastic cable ties!
- Integrated outgoing patchcord clamps and routing guides, which ensures min bend radius criteria of 35 mm and professional cable management.



Each U accommodates 2 fiber trays Integrated patchcord mandrels



Pull-Out Cassette System

#### Options

• 1U Module with 48 fibers

## **Technical Details**

Dimensions	486 mm (W) x 258 mm (D) x 133 mm (H)
Material	Mild Steel
Color	Powder coat RAL7035
Weight	4 kg
Maximum Port Capacity	144 Ports for SSF Double Connectors

### **Applications**

Carrier&transmission networks in central offices of Telco`s, Outside cabinet applications, FTTX applications, Utility Networks (WAN&MAN)



Special Incoming fiber tube fixing system

Follow Us!

in

# **CAN-TROY-700 Technical Drawing**





## CANOVATE

# **CAN-TROY-700** Cassette Options

### 1-Double Sided Splice & Patch Cassette CAN-TROY-700-SP

### Highlights

- LSZH flame retardant
- 24 Port for SFF adaptors (LC/E2000)
- 12 Port for other adaptors (SC/ST/FC)



2-Splitter Cassette CAN-TROY-700-ST

### Highlights

- LSZH flame retardant
- 1x2, 1x4, 1x8, 1x16 Splitters can be installed





## Highlights

- LSZH flame retardant
- 24 port splice







